

# PORĘBA

## UCHWYTY SAMOCENTRUJĄCE STALOWE

Mocowanie	Ilość szczęk	Rodzaj szczęk	Typ	Średnica uchwytu D [mm]										
				80	100	125	160	200	250	315	400	500	630	800
<b>DIN 6350</b>			T105				X	X	X	X	X			
			T504	X	X	X	X	X	X	X	X	X	X	
			T574	X	X	X	X	X	X	X	X	X	X	
			T505			X	X	X	X	X	X	X	X	
			T575			X	X	X	X	X	X	X	X	
			T704		X	X	X	X	X	X	X	X	X	
			T774			X	X	X	X	X	X	X		
			T705			X	X	X	X	X	X	X		
			T775			X	X	X	X	X	X	X		
			T806					X	X	X	X	X		
T807							X	X	X	X	X			
				80	100	125	160	200	250	315	400	500	630	800
<b>DIN 55026</b> Dostępne Nr stożków			T514				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
			T515				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
			T714				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
			T715				5	5;6	5;6;8	6;8	6;8;11	8;11	11;15	
				80	100	125	160	200	250	315	400	500	630	800
<b>DIN 55027</b> Dostępne Nr stożków			T534			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
			T535			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
			T734			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
			T735			3;4	4;5	5;6	6;8	6;8;11	8;11	8;11	11;15	
				80	100	125	160	200	250	315	400	500	630	800
<b>DIN 55029</b> Dostępne Nr stożków			T544			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
			T545			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
			T744			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
			T745			3;4	3;4;5	4;5;6	6;8	6;8;11	8;11	8;11	11;15	
				80	100	125	160	200	250	315	400	500	630	800
<b>Set-Tru</b>			T564			X	X	X	X	X	X	X	X	
			T565			X	X	X	X	X	X	X	X	X
			T864			X	X	X	X	X	X	X	X	
			T865			X	X	X	X	X	X	X	X	
										315	405	515	630	
<b>Oil Chucks</b>			T597								X	X		

PN-EN ISO 9001 : 2009

Certyfikat ISO Nr 44100132840,

TÜV NORD

**Korpus** - stal C45,  
28±2 HRC ;

**Tarcza spiralna** - 42CrMo4 (40HM),  
60±2 HRC;

**Szczęki** - 20MnCr5 (18HGT),  
50±2 HRC;

**Kółka zębate** - 16MnCr5 (16HG),  
48±2 HRC.

**Smar Gleitmo 805.**

