

# Fabryka Narzędzi POREBA Sp. z o.o.

ul. Zakładowa 2A, 42-480 Poręba, Polska, tel/fax 48-32 6466231  
NIP 649 229 43 63, REGON 242725490, KRS 0000404769



## 3-Jaw self-centering steel body lathe chucks

# Ø160 mm



### Cylindric fixing DIN 6350

|  |                    |  |                              |  |
|--|--------------------|--|------------------------------|--|
|  | Fixing             |  | Chuck with <b>solid jaws</b> | Chuck with <b>2-pieces reversible jaws</b> |
|  | from back          |  | T504-160                     | T505-160                                   |
|  | from back or front |  | T574-160                     | T575-160                                   |

### Type A fixing DIN 55026

|  |                       |          |      |                              |  |
|--|-----------------------|----------|------|------------------------------|--|
|  | 1:4 spindel nose size | B - max. | F    | Chuck with <b>solid jaws</b> | Chuck with <b>2-pieces reversible jaws</b> |
|  | 5                     | 82,573   | 61,9 | T514-160-5                   | T515-160-5                                 |

### Type C with bayonet ring fixing DIN 55027

|  |                       |          |       |                              |  |
|--|-----------------------|----------|-------|------------------------------|--|
|  | 1:4 spindel nose size | B - max. | F     | Chuck with <b>solid jaws</b> | Chuck with <b>2-pieces reversible jaws</b> |
|  | 3                     | 53,985   | 75,5  | T534-160-3                   | T535-160-3                                 |
|  | 4                     | 63,525   | 85,0  | T534-160-4                   | T535-160-4                                 |
|  | 5                     | 82,573   | 104,8 | T534-160-5                   | T535-160-5                                 |

### Type D Camlock fixing DIN 55029

|  |                       |          |        |                              |  |
|--|-----------------------|----------|--------|------------------------------|--|
|  | 1:4 spindel nose size | B - max. | F      | Chuck with <b>solid jaws</b> | Chuck with <b>2-pieces reversible jaws</b> |
|  | 3                     | 53,985   | 70,66  | T544-160-3                   | T545-160-3                                 |
|  | 4                     | 63,525   | 82,55  | T544-160-4                   | T545-160-4                                 |
|  | 5                     | 82,573   | 104,80 | T544-160-5                   | T545-160-5                                 |